

G2052 - Caterpillar

STATUS

På lager

REF. NR.

G2052

MANUFACTURE

Caterpillar

ENGINE

Caterpillar 3408 410 hp. 1800 rpm Serie 67U3015

GENERATOR

Nishishiba Type NTAKL

VOLT

440

KVA

250

HZ

60

REMARKS

Price without Allweiler pump





**OPERATING LIMITS
AT RATED SPEED AND LOAD**

JACKET WATER	160°-210°	
	71°-99°	
EXHAUST STACK	800	F° MAX
TEMP	427	C° MAX
MANIFOLD AIR	235	F° MAX
	112.8	C° MAX
AIR CLEANER	30	IN. H ₂ O
RESTRICTION	74.72	cmH ₂ O
ENGINE OIL	160-230	°F
	71.1-110.0	°C
ENGINE OIL	50	PSI MIN
	3.5	kg/cm ² MIN
OIL FILTER		PSI MAX
DIFFERENTIAL		kg/cm ² MAX
FUEL	25-40	PSI
	1.8-2.8	kg/cm ²
GEAR OIL		°F
		°C
GEAR OIL		PSI
		kg/cm ²
ENGINE SERIAL		
NO.	67U3015	

EQUIPMENT OPERATING UNDER NORMAL OR AVERAGE OPERATING CONDITIONS SHOULD INDICATE READINGS WITHIN THE LIMITS LISTED. PERIODIC RECORDING OF THESE INSTRUMENT READINGS STARTING WITH...

