

STATUS	På lager
REF. NR.	HP23
PUMP MANUFACTURE	Voith
PUMP TYPE	IPH 6-80
PUMP PRESSURE (BAR)	260
PUMP FLOW (LITER/MIN.)	121,9
MOTOR MANUFACTURE	Asea MBM 250 M4
MOTOR KW	50
MOTOR VOLT	440
MOTOR RPM	1465



ASEA MADE IN SWEDEN
FABRIQUÉ EN SUÈDE

Motor MEM 250 M-4

3~ 50 Hz No. 7127 522

50 kW 1465 r/min

Cl. F cos φ 0.89

Prim.  V Prim.  440 V

Y  A Δ  80 A

Sec. V A

Cat. no. IP 54 320 kg

SEN 2601 IEG 34-1

SMÖRJ. vid första start tills fett tränger ut ur fettutloppet. Torka nipplarna renat!
LUBRICATE at first start until grease is forced out of the outlet. Clean the nipples!

SMÖRJ under drift varje lager med kullagerfett.
LUBRICATE when running with ball bearing grease.

Fettmängd per lager Quantity per bearing	Drift Service	Smörjintervall Lubr. interval
60 g	8 h	12 mån. month
	24 h	6 mån. month

121284

VOITH

VOITH GETRIEBE KG
HEIDENHEIM

Typ IP 11 0-80

P max = 300 bar

n max = 2500 1/min

LIZENZ ECKERLE