

STATUS

På lager

REF. NR.

LP250

MANUFACTURE

Azcue

TYPE

BT/LV 100T 01 no plate

REMARKS

ABB motor. 22/25 kW, 50/60 Hz, 980/1180 rpm, 440 volt





Dimensiones Dimensions Dimensions

Tipo / Type BT-LV N. 776-LV80125

Azcue BT/LV 100T 01

Basic Pump	Tipo	Motor / Moteur		a	b	c	d	e	f	g	h	k	m	x	y	DN/DN2	Q	kg (a)	
		R.p.m. / U/min.	1410																
LV MT HT	100T	1.1	1.2	1070	110	270	300											140	170
	100T	2.2	2.5	1130	115	270	300											140	170
	100T	3	3.5	1190	120	270	300											140	170
	100T	4.5	5.5	1250	125	270	300											140	170
	100T	7.5	9	1310	130	270	300											140	170
	100T	11	13	1370	135	270	300											140	170
	100T	15	18	1430	140	270	300											140	170
	100T	22	27	1490	145	270	300											140	170
	100T	30	36	1550	150	270	300											140	170
	100T	45	55	1610	155	270	300											140	170
LV 12FT	100T	1.1	1.2	1070	110	270	300											140	170
	100T	2.2	2.5	1130	115	270	300											140	170
	100T	3	3.5	1190	120	270	300											140	170
	100T	4.5	5.5	1250	125	270	300											140	170
	100T	7.5	9	1310	130	270	300											140	170
	100T	11	13	1370	135	270	300											140	170
	100T	15	18	1430	140	270	300											140	170
	100T	22	27	1490	145	270	300											140	170
	100T	30	36	1550	150	270	300											140	170
	100T	45	55	1610	155	270	300											140	170

Sujeto a cambios / Subject to alterations / Sujet a des modifications

* En el peso indicado no está incluido el motor
The stated weight does not include the motor
Le poids total indiqué n'inclut pas le moteur

(1) Conexión varicorona. / Variable connection. / Connexion varicorona.
(2) Conexión manómetro. / Manometer connection. / Connexion manometre.

DIN 2501, Pn10/16

DN	125	150	200
K ⁿ	210	240	295
D ^p	250	285	340
N ⁿ	8	8	8
d	18	22	22

Pa16 Pa10

www.northridgepumps.com

Bombas Azcue UK Supplier

bombas-azcue

Supplier of Azcue pumps and spares to the UK and International

Azcue BT-LV Vertical Triple Screw Pump

Vertical self priming long coupled triple screw pumps.
Designed for pumping lubricant media and gasoil, diesel, fuel transfer and feed applications.

- Flow rates up to 200m³/hr
- Head up to 10bar
- Port sizes range from DN 125mm to 200mm
- Temperature up to +160°C
- Available in Cast Iron GG-25 and Ductile Cast Iron GGG40 (Versions MT/HT).

Azcue BT-LV Pump model numbers:
BT-LV80, BT-LV90, BT-LV100, BT-LV110, BT-LV125

For price and technical information, please contact us at sales@bombas-azcue.co.uk

1/1



