

ABB - AMA 450L 8L VAFMH

| | |
|-------------|---|
| STATUS | På lager |
| REF. NR. | M2341 |
| MANUFACTURE | ABB |
| TYPE | AMA 450L 8L VAFMH |
| ENGINE NO. | 4596451 |
| HP | 1608 |
| RPM | 892 |
| YEAR | 2009 |
| REMARKS | Unused electro propulsion N.V. HEL09-6280 4596451 |





ABB Oy
Made in Hungary, Poland

| | | | |
|--------------|------------------|--------|---------|
| Type | AMA 450L8L VAFMH | No | 4596451 |
| Year | 2009 | Phases | 3~ |
| Connection D | Insul.cl. F | Duty | S1 |
| IP | 55 | Weight | 4810 kg |
| | IC | B1W | IM 4011 |

S1 CONVERTER SUPPLY, ACS

| | | |
|---|---------|-----|
| 0 | - 1200 | kW |
| 0 | - 660 | V |
| 0 | - 1300 | A |
| 0 | - 0.84 | PF |
| 0 | - 60 | Hz |
| 0 | - 892.1 | rpm |

Ambient 45°C
Cooling water 38°C
Cooling water flow 7.2 m³/h

IEC 60034-1

| | |
|--|--------------------|
| DRIVE END (D) BEARING | 6326/C3 |
| NON DRIVE END (N) BEARING | 7322 B |
| LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE | 4400 DUTY HOURS |
| QUANTITY OF GREASE | DE 80 GRAMS NDE 80 |

(NOTE) EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.
(NOTE) ABOVE 80°C (180°F) HIGH TEMPERATURE GREASE SHALL BE USED.

DELIVERED FROM FACTORY WITH GREASE ESSO LUBRE X N2
FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL