

# ABB - AMA 500L 6L VAFTMH

STATUS	På lager
REF. NR.	M2346
MANUFACTURE	ABB
TYPE	AMA 500L 6L VAFTMH
ENGINE NO.	4606317
HP	2587
RPM	906
YEAR	2010
REMARKS	Unused electro propulsion





ABB

CE

ABB Oy  
Made in Finland

Type	AMA 500L6L VAPTMH	No	4606317
Year	2010	Phases	3~ Duty S1
Connection D	Insul.cl. F	Weight	64.30 kg
IP	55	IC	85W <sub>8</sub> IM 4011

ST. CONVERTER SUPPLY, ACS

0	- 1930	- 0	- 0	- 0	kw
0	- 690	- 0	- 0	- 0	V
0	- 1903	-	-	-	A
0	- 0.88	- 0	- 0	- 0	PF
0	- 45.7	- 0	- 0	- 0	Hz
0	- 906.3	- 0	- 0	- 0	rpm

Ambient temp. 45 °C  
 Max. cooling water temp. 38 °C  
 Cooling water flow 10.4 m<sup>3</sup>/h

IEC 60034-1

DRIVE END (DE) BEARING

NON DRIVE END (NDE) BEARING

LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE  DUTY HOURS

QUANTITY OF GREASE DE  GRAMS NDE  GRAMS

NOTE! EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.

NOTE! ABOVE 80°C (180°F) HIGH TEMPERATURE GREASE SHALL BE USED.

DELIVERED FROM FACTORY WITH GREASE

FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL