

# ABB - AMA 500L 6L BAFMH

STATUS

På lager

REF. NR.

M2347

MANUFACTURE

ABB

TYPE

AMA 500L 6L BAFMH

ENGINE NO.

4596464

HP

2010

RPM

1201

YEAR

2008

REMARKS

Unused electro propulsion





**ABB** CE **ABB Oy**  
Made in Helsinki, Finland

Type	AMA 500L6L BAFMH		No	4596464	
Year	2008	Phases	3~	Duty	S1
Connection D	Insul.cl. F		Weight		5340 kg
IP	55	IC	81W	IM	1001

**S1 CONVERTER SUPPLY, ACS**

0	- 1500				
0	- 660				kw
0	- 1535				V
0	- 0.88				A
0	- 60.4				PF
0	- 1201.3				Hz
0					rpm

Amb. 45°C  
Cooling water temp. 38°C  
Cooling water flow 7.6 m³/h

IEC 60034-1

DRIVE END (DE) BEARING	6330/C3	
NON DRIVE END (NDE) BEARING	6324/C3	
LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE	6600	DUTY HOURS
QUANTITY OF GREASE	DE 100 GRAMS	NDE 100 GRAMS

NOTE: EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.  
NOTE: ABOVE 85°C (185°F) HIGH TEMPERATURE GREASE SHALL BE USED.

DELIVERED FROM FACTORY WITH GREASE

FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL

