

<b>STATUS</b>	Available
<b>REF. NUMBER</b>	HP23
<b>PUMP MANUFACTURE</b>	Voith
<b>PUMP TYPE</b>	IPH 6-80
<b>PUMP PRESSURE (BAR)</b>	260
<b>PUMP FLOW (LITER/MIN.)</b>	121,9
<b>MOTOR MANUFACTURE</b>	Asea MBM 250 M4
<b>MOTOR KW</b>	50
<b>MOTOR VOLT</b>	440
<b>MOTOR RPM</b>	1465



**ASEA** MADE IN SWEDEN  
FABRIQUÉ EN SUÈDE

Motor MEM 250 M-4

3~ 50 Hz No. 7127 522

50 kW 1465 r/min

Cl. F cos φ 0.89

Prim.  V Prim.  440 V

Y  A  80 A

Sec. V A

Cat. no. IP 54 320 kg

SEN 2601 IEG 34-1

SMÖRJ. vid första start tills fett tränger ut ur fettutloppet. Torka nipplarna renat!  
LUBRICATE at first start until grease is forced out of the outlet. Clean the nipples!

SMÖRJ under drift varje lager med kullagerfett.  
LUBRICATE when running with ball bearing grease.

Fettmängd per lager Quantity per bearing	Drift Service	Smörjintervall Lubr. interval
60 g	8 h	12 mån. month
	24 h	6 mån. month

121284

**VOITH**

VOITH GETRIEBE KG  
HEIDENHEIM

Typ IP 11 0-80

P max = 300 bar

n max = 2500 1/min

LIZENZ ECKERLE