

M2346 - ABB

STATUS	Available
REF. NUMBER	M2346
MANUFACTURE	ABB
TYPE	AMA 500L 6L VAFTMH
ENGINE NO.	4606317
HP	2587
RPM	906
YEAR	2010
REMARKS	Unused electro propulsion





ABB

CE

ABB Oy
Made in Finland - 15,0000 Helsinki, Finland

Type	AMA 500L6L VAPTMH	No	4606317		
Year	2010	Phases	3~	Duty	S1
Connection D		Insul.cl.	F	Weight	64.30 kg
IP	55	IC	86W*	IM	4011

ST CONVERTER SUPPLY, ACS

0	- 1930	- 0	- 0	- 0	kW
0	- 690	- 0	- 0	- 0	V
0	- 1903	-	-	-	A
0	- 0.88	- 0	- 0	- 0	PF
0	- 45.7	- 0	- 0	- 0	Hz
0	- 906.3	- 0	- 0	- 0	rpm

Ambient temp. 45 °C
Max. cooling water temp. 38 °C
Cooling water flow 10.4 m³/h

IEC 60034-1

DRIVE END (DE) BEARING

NON DRIVE END (NDE) BEARING

LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE DUTY HOURS

QUANTITY OF GREASE DE GRAMS NDE GRAMS

NOTE! EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.

NOTE! ABOVE 80°C (180°F) HIGH TEMPERATURE GREASE SHALL BE USED.

DELIVERED FROM FACTORY WITH GREASE

FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL