

ABB - AMA 500L 6L BAFMH

STATUS	Available
REF. NUMBER	M2347
MANUFACTURE	ABB
TYPE	AMA 500L 6L BAFMH
ENGINE NO.	4596464
HP	2010
RPM	1201
YEAR	2008
REMARKS	ABB, AMA 500L 6L BAFMH, Unused electro propulsion





ABB CE **ABB Oy**
Made in Helsinki, Finland

Type	AMA 500L6L BAFMH		No	4596464	
Year	2008	Phases	3~	Duty	S1
Connection D	Insul.cl. F		Weight	5340 kg	
IP	55	IC	81W	IM	1001

S1 CONVERTER SUPPLY, ACS

0	- 1500	kw
0	- 660	V
0	- 1535	A
0	- 0.88	PF
0	- 60.4	Hz
0	- 1201.3	rpm

Amb. 45°C
Cooling water temp. 38°C
Cooling water flow 7.6 m³/h

IEC 60034-1

DRIVE END (DE) BEARING	6330/C3	
NON DRIVE END (NDE) BEARING	6324/C3	
LUBRICATION INTERVAL AT 70°C (158°F) BEARING TEMPERATURE	6600	DUTY HOURS
QUANTITY OF GREASE	DE 100 GRAMS	NDE 100 GRAMS

NOTE: EVERY 15°C (27°F) INCREASE ABOVE 70°C (158°F) IN THE BEARING TEMPERATURE HALVES THE RATED LUBRICATION INTERVAL.
NOTE: ABOVE 85°C (185°F) HIGH TEMPERATURE GREASE SHALL BE USED.

DELIVERED FROM FACTORY WITH GREASE **ES50 UNIREX H2**
FOR ADDITIONAL INFORMATION SEE MAINTENANCE MANUAL

